

Model 750 1-Hose Wash Water Recycling System



The Model 750 is a 1-Hose wash water recycle system designed to handle the equipment wash operation of a typical 9-hole, or small 18-hole golf course. For optimal performance, the Model 750 is designed to be used in conjunction with ESD Waste2Water's pre-engineered Clipping Separation System and in-ground sumps. The Model 750 can readily be modified to accommodate remote hose stations, and can be customized to easily update existing wash areas. The system is versatile, requires low maintenance and is extremely effective at recycling wash water from turf care facility wash areas.

Model 750 Specifications:


Flow Range:	0-15 GPM
Daily Throughput:	1,250 GPD
Electrical:	230 Volt 1 Phase 40 amp
Fresh Water Supply:	3/4" line required
Operating Capacity:	598 gallons
Biological Media:	1,152 sq ft
Pressure Pump: (Centrifugal)	3/4 hp
Regenerative Blower:	1.5 hp
Dimensions: (L x W x H)	7' x 4' x 4'3"
Net Weight:	450 lbs



Certified to UL-508A Standards



System Wash Water Flow Diagram and Description



- A Round Sump**
Wash water flows into a pre-engineered ESD Round Sump. Water, grass clippings and sand are swooshed around into a slurry. A powerful pump then pushes the slurry to the Clipping Separator.
- B Clipping Separator**
The wash water slurry flows over the fine mesh clipping screen where grass and other solids slide down the clipping screen and into the Clipping Cart. At the same time, water drops through the clipping screen and into the Solids Separator.
- C Clipping Cart**
The clipping cart captures grass clippings, sand particulates and other solids. The solids are dewatered as they drip-dry in the Clipping Cart. The water drains into a Shallow Sump below the Clipping Cart. Once dewatered, the grass clippings are removed and disposed of appropriately.
- D Shallow Sump**
Below the Clipping Cart a Shallow Sump collects excess water where it is drained back to the Round Sump.

- E Solids Separator**
Wash water from the Clipping Separator flows through a series of baffles and then gravity-feeds into the Biological Treatment System. Fine solids settle, and are drained on a regular basis, through valves in the bottom of the Solids Separator. The solids are then deposited into the Clipping Cart for disposal.
- F Biological Treatment System**
Once in the Biological Treatment System, the water travels over and under a series of baffles and through a mass of honeycomb biomedia covered with specially-formulated microbes. Organic contaminants are consumed by the microbes, and the contaminants are converted into carbon dioxide and water.
- G Recycled Wash Water**
Treated water is delivered, with a powerful pump, to the wash hoses and nozzles provided by ESD. The equipment is then washed with forceful streams of recycled wash water.



495 Oak Road
Ocala, Florida 34472
Tel: 800.277.3279 • Fax: 352-680-9278
www.waste2water.com

